

## Monitoring system

testo 160 IAQ – Monitoring system for temperature, humidity, atmospheric pressure and CO<sub>2</sub> concentration.

---

Measurement value transfer by wireless LAN to the Cloud store

---

Measurement values can be called up on all end devices

---

Alarm notification by SMS or e-mail

---

Inconspicuous design and small dimensions

---

Deco-cover for optimum individual adaptation of the logger to the surroundings

---



The WiFi data logger testo 160 IAQ monitors the ambient conditions temperature, humidity, atmospheric pressure and the CO<sub>2</sub> concentration in buildings such as public facilities, office complexes and education institutions. The logger transfers measurement values by wireless LAN to the online store (Testo Cloud). You can access all data at any time via your normal browser on your PC/tablet/smartphone. If limit values are exceeded, an alarm is immediately provided by SMS and/or e-mail.

Thanks to the optional, individually designable deco-cover, the logger can be integrated inconspicuously in buildings. The testo 160 IAQ thus enables you to check all relevant ambient conditions and fulfil the obligation of documentation.

# The testo 160 Cloud

## Our packages

The testo 160 Cloud is the central operating element of the testo 160 monitoring system. Here you can configure your WiFi data loggers, set limit value alarms and analyze measurement data. You must first register at [www.saveris2.net](http://www.saveris2.net) to have access to the testo 160 Cloud.

Depending on the range of functions you require, you have a choice between the free Basic and the more extensive Advanced functionality.

	Basic	Advanced
<b>Measuring cycle</b>	15 min. to 24 h	1 min. to 24 h (Battery mode: 5 min to 24 h)
<b>Communication cycle</b>	15 min. to 24 h	1 min. to 24 h (Battery mode: 5 min to 24 h)
<b>Data storage</b>	Max. 3 months	Max. 2 years
<b>Reports</b>	Manual (.pdf/.csv)	Manual (.pdf/.csv) Automatic (.pdf/.csv)
<b>Data analysis</b>	For one measurement site each (external probes count as measurement sites)	For up to 10 measurement channels simultaneously
<b>Number of users per account</b>	1	10
<b>Number of WiFi data loggers per account</b>	Unlimited	Unlimited
<b>Alarm options</b>	Upper/lower alarm limits	<ul style="list-style-type: none"> <li>• Upper/lower alarm limits</li> <li>• Alarm delay</li> <li>• Time control of alarms</li> </ul>
<b>System notifications</b>	<ul style="list-style-type: none"> <li>• Notification of low battery</li> <li>• Radio link interrupted</li> <li>• Power supply interrupted</li> </ul>	<ul style="list-style-type: none"> <li>• Notification of low battery</li> <li>• Radio link interrupted</li> <li>• Power supply interrupted</li> </ul>
<b>E-mail alarm</b>	Yes	Yes
<b>Multiple recipients for alarm e-mails</b>	Yes (up to 3)	Yes (unlimited)
<b>SMS alarm</b>	No	<ul style="list-style-type: none"> <li>• Including 25 SMS per logger and year</li> <li>• More SMS packages purchasable</li> </ul>
<b>Duration</b>	Unlimited	12 month license: Order no. 0526 0735

## Ordering data/technical data

### testo 160 IAQ

testo 160 IAQ WLAN air quality logger with display and built-in sensors for temperature, humidity, CO<sub>2</sub> and atmospheric pressure, including free cloud access (Basic functionality), USB cable, batteries (4 x AA Alkaline-Manganese), wall bracket including unlocking tool and adhesive strips, QR code sticker, calibration protocol and short instructions



Order no. 0572 2014

## Accessories

	Order no.	
Deco-cover for testo 160 IAQ	0554 2012	
Wall bracket for testo 160 IAQ	0554 2015	
Alkaline manganese mignoncell AA batteries up to -10 °C, order 4 off	0515 0414	
Mains unit for testo 160 radio data logger	0572 2020	
ISO calibration certificate temperature +15 °C, +25 °C, +35 °C	0520 0172	
ISO calibration certificate humidity at +25 °C, humidity points 11.3 %RH and 75.3 %RH	0520 0076	
ISO calibration certificate CO <sub>2</sub> , calibration points 0; 1000; 5000 ppm	0520 0033	

<b>Temperature measurement</b>	
Measuring range	0 to +50 °C
Accuracy	± 0.5 °C
Resolution	0.1 °C
<b>Humidity measurement</b>	
Measuring range	0 to 100 %RH (non-condensing)
Accuracy	±2 %RH at +25 °C and 20 to 80 %RH ±3 %RH at +25 °C and < 20 %RH and > 80 %RH ±1 %RH hysteresis ±1 %RH / year drift
Resolution	0.1% RH
<b>CO<sub>2</sub> measurement</b>	
Measuring range	0 to 5,000 ppm Ambient humidity: 0 to 99 %RH (non-condensing)
Accuracy	±(50 ppm + 3 % of m.v.) at +25 °C Without external power supply: ±(100 ppm + 3 % of m.v.) at +25 °C
Resolution	1 ppm
<b>Pressure measurement</b>	
Measuring range	600 to 1100 mbar
Accuracy	±3 mbar at +22 °C
Resolution	1 mbar
<b>WLAN</b>	
Standard	802.11 b/g/n
Security	WPA2 Enterprise: EAP-TLS, EAP-TTLS-TLS, EAP-TTLS-MSCHAPv2, EAP-TTLS-PSK, EAP-PEAP0-TLS, EAP-PEAP0-MSCHAPv2, EAP-PEAP0-PSK, EAP-PEAP1-TLS, EAP-PEAP1-MSCHAPv2, EAP-PEAP1-PSK, WPA Personal, WPA2 (AES), WPA (TKIP), WEP
<b>General</b>	
Operating temperature	0 to +50 °C
Storage temperature	0 to +50 °C
Protection class	IP20
Measuring cycle	Dependent on Cloud licence Basic: 15 min to 24 h Advanced: 1 min to 24 h / with battery operation: 5 mins to 24 h
Communication cycle	Dependent on Cloud licence Basic: 15 min to 24 h Advanced: 1 min to 24 h
Memory	32,000 readings (sum of all channels)
Alarm function	LED traffic light function green, amber, red (in battery mode, the traffic light only lights up during the measurement. When using the USB mains unit, the traffic light function is permanently active.)
Voltage supply (alternatively mains unit via USB connection)	4 x AA alkaline manganese batteries 1.5 V
Battery life (depending on the measuring and communication cycle vis-a-vis the Cloud)	1 year
Dimensions	117 x 82 x 32 mm
Weight (including batteries)	269 g



Hassellunden 11A, 2765 Smørum  
Tel. 45 95 04 10  
info@buhl-bonsoe.dk  
www.buhl-bonsoe.dk