

# Non-contact voltage tester

testo 745

---

Filter for high-frequency interference signals

---

Adjustable sensitivity

---

Visual and acoustic signal

---

Waterproof and dustproof according to IP 67

---

Measuring point illumination

---



The testo 745 non-contact voltage tester with a voltage range of up to 1,000 V AC is particularly well-suited to fast initial checking of any suspected fault sources. When the presence of alternating current is determined, the testo 745 gives a warning via a clear visual and acoustic signal.

In order to increase reliability, the voltage tester has a filter for high-frequency interference signals and is also waterproof and dustproof according to IP 67.

## Technical data/accessories

### testo 745

testo 745, non-contact voltage tester  
including batteries

Order no. 0590 7450



#### Technical data

|                              |                                 |
|------------------------------|---------------------------------|
| Voltage testing              | 12 to 1,000 V AC                |
| Measuring point illumination | ✓                               |
| Measurement category         | CAT IV 600 V<br>CAT III 1,000 V |
| Protection class             | IP 67                           |
| Operating temperature        | -10 to +50 °C                   |
| Storage temperature          | -15 to +60 °C                   |
| Dimensions                   | 155 x 25 x 23 mm (L x W x H)    |
| Weight                       | 63 g                            |
| Authorizations               | CSA, CE                         |
| Standards                    | EN 61326-1, EN 61010-1          |

1981 1514/msp/I/01.2018

#### Accessories

#### Order no.

|  |           |  |
|--|-----------|--|
| ISO calibration certificate voltage tester   | 0520 0750 |  |
| DAkkS calibration certificate voltage tester | 0520 0751 |  |

Subject to change without notice.



Hassellunden 11A, 2765 Smørum  
Tel. 45 95 04 10  
info@buhl-bonsoe.dk  
www.buhl-bonsoe.dk